

ID: **C23030** 

Cu Copper 7440-50-8 84.7% Zn Zinc 1314-13-2 15.0% Si Silicon 7440-21-3 0.3%  SECTION 4 – FIRST AID MEASURES  EYE CONTACT: Eye injuries from solid particles should receive immediate medical attention. Dust may be flushed from eyes immediately with large amounts of water, lifting the lower and upper lids occasionally; seek medical attention.  Cuts or abrasions should be treated promptly with thorough cleansing of the affected area. Wash the skin using soap or mild detergent and water. Get medical attention if irritation develops and persists.  INGESTION: If the product or dust is swallowed, seek immediate medical attention or advice. Do rinduce vomiting.  If breathing has stopped, perform artificial respiration and obtain medical aid immediately. If breathing is difficult, provide fresh air and seek medical attention as			A UNITED STARS CO.			
PRODUCT NAME:  C23030 MODIFIED RED BRASS METAL COPPER ALLOY  OTHER DESIGNATIONS:  PRODUCT IDENTIFICATION:  THE ELECTRIC MATERIALS COMPANY 50 SOUTH WASHINGTON STREET NORTH EAST, PA 16428  EMERGENCY PHONE NO.:  814-725-9621  WEBSITE: WWW.ELECMAT.COM  RECOMMENDED USE AND RESTRICTIONS ON USE: Manufacturing & Industry for non-structural components predominantly to conduct electrical current.  SECTION 2 - HAZARD IDENTIFICATION  Copper and copper alloys are considered on "article" and not hazardous in its solid from. However, certain processes such as cutting, milling, grinding, melt and welding could result in some hazardous materials being emitted.  Fumes from hot processes may contain other compounds with differe exposure limits. Dust or fumes generated by machining, grinding, welding or thermal cutting of the copper may produce airborne contaminants. Consult Sections 3 & 8 for further information.  SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS  CHEMICAL NAME  CU  COPPER TA40-50-8  84.7% 2n  Zinc  1314-13-2  15.0% 3ii Silicon  7440-21-3  0.3%  SECTION 4 - FIRST AID MEASURES  Eye injuries from solid particles should receive immediate medical attention. Dust may be produce airborne and upper lids occasionally; seek medical attention.  Cuts or abrasions should be treated promptly with thorough cleansing of the affected area. Wash the skin using soap or mild detergent and water. Get medical attention if irritation develops and persists.  INGESTION:  If the product or dust is swallowed, seek immediate medical attention or advice. Dor induce vomiting.  If preathing has stopped, perform artificial respiration and obtain medical aid immediately. If breathing has stopped, perform artificial respiration and seek medical attention as immediately. If breathing has stopped, perform artificial respiration and obtain medical aid immediately. If breathing has stopped, perform artificial respiration and obtain medical aid immediately. If breathing has stopped, perform artificial respiration and obtain medical aid immediately.				DATE ISSUE	ED: <b>5/28</b>	3/2015
AND THE DESIGNATIONS:  PRODUCT IDENTIFICATION:  Copper and Copper Alloys  THE ELECTRIC MATERIALS COMPANY 50 SOUTH WASHINGTON STREET NORTH EAST, PA 16428  EMERGENCY PHONE NO.:  814-725-9621  WEBSITE: WWW.ELECMAT.COM  RECOMMENDED USE AND RESTRICTIONS ON USE: Manufacturing & Industry for non-structural components predominantly to conduct electrical current.  SECTION 2 — HAZARD IDENTIFICATION  Copper and copper alloys are considered on "article" and not hazardous in its solid from. However, certain processes such as cutting, milling, grinding, melt and welding could result in some hazardous materials being emitted.  Fumes from hot processes may contain other compounds with differe exposure limits. Dust or fumes generated by machining, grinding, welding or thermal cutting of the copper may produce airborne contaminants. Consult Sections 3 & 8 for further information.  SECTION 3 — COMPOSITION/INFORMATION ON INGREDIENTS  CHEMICAL NAME  CU  COPPER 7440-50-8 84.7% 2n 2inc 1314-13-2 15.0% 2inc 1314-13-2 15.0% 3iiicon 7440-21-3 0.3%  SECTION 4 — FIRST AID MEASURES  Eye injuries from solid particles should receive immediate medical attention. Dust may be flushed from eyes immediately with large amounts of water, lifting the lower and upper lids occasionally; seek medical attention.  Cuts or abrasions should be treated promptly with thorough cleansing of the affected area. Wash the skin using soap or mild detergent and water. Get medical attention if irritation develops and persists.  INGESTION:  If the product or dust is swallowed, seek immediate medical attention or advice. Do not induce vomiting.  If breathing has stopped, perform artificial respiration and obtain medical aid immediately. If breathing has stopped, perform artificial respiration and obtain medical aid immediately. If breathing is difficult, provide fresh air and seek medical attention as immediately. If breathing has stopped, perform artificial respiration and obtain medical aid immediately. If breathing is difficult, provide fresh air and seek medical at	SEC	TION 1 -	- PRODUCT IDENTIFICATION & COM	IPANY INFORM	MATION	
MANUFACTURER'S INFORMATION:  THE ELECTRIC MATERIALS COMPANY SO SOUTH WASHINGTON STREET NORTH EAST, PA 16428  EMERGENCY PHONE NO.:  814-725-9621  WEBSITE: WWW.ELECMAT.COM  RECOMMENDED USE AND RESTRICTIONS ON USE: Manufacturing & Industry for non-structural components predominantly to conduct electrical current.  SECTION 2 – HAZARD IDENTIFICATION  Copper and copper alloys are considered on "article" and not hazardous in its solid from. However, certain processes such as cutting, milling, grinding, melt and welding could result in some hazardous materials being emitted.  OTHER INFORMATION:  OTHER INFORMATION:  SECTION 3 – COMPOSITION/INFORMATION ON INGREDIENTS  CHEMICAL NAME  CU  Copper  CU  Copper  CU  Copper  CU  Copper  COMMON NAME  CAS # PERCENT WEIGH  CU  Copper  A440-50-8  84.7%  Zn  Zinc  Silicon  T440-50-8  84.7%  Zn  Zinc  Silicon  SECTION 4 – FIRST AID MEASURES  Eye injuries from solid particles should receive immediate medical attention. Dust may be flushed from eyes immediately with large amounts of water, lifting the lower and upper lids occasionally; seek medical attention.  Cuts or abrasions should be treated promptly with thorough cleansing of the affected area. Wash the skin using soap or mild detergent and water. Get medical attention if irritation develops and persists.  INGESTION:  If the product or dust is swallowed, seek immediate medical attention or advice. Do rinduce vomiting.  If breathing has stopped, perform artificial respiration and obtain medical aid immediately. If breathing is difficult, provide fresh air and seek medical attention as immediately. If breathing is difficult, provide fresh air and seek medical attention as immediately. If breathing is difficult, provide fresh air and seek medical attention as immediately. If breathing is difficult, provide fresh air and seek medical attention as immediately. If breathing is difficult, provide fresh air and seek medical attention as immediately. If breathing is difficult, provide fresh air and seek medical attention as immediately. If	PRODU	CT NAMI	E: C23030 MODIFIED RED BRASS N	METAL COPPE	R ALLOY	
THE ELECTRIC MATERIALS COMPANY SO SOUTH WASHINGTON STREET NORTH EAST, PA 16428  EMERGENCY PHONE NO.: 814-725-9621 WEBSITE: WWW.ELECMAT.COM  RECOMMENDED USE AND RESTRICTIONS ON USE: Manufacturing & Industry for non-structural components predominantly to conduct electrical current.  SECTION 2 — HAZARD IDENTIFICATION  COpper and copper alloys are considered on "article" and not hazardous in its solid from. However, certain processes such as cutting, milling, grinding, melt and welding could result in some hazardous materials being emitted.  Fumes from hot processes may contain other compounds with differe exposure limits. Dust or fumes generated by machining, grinding, welding or thermal cutting of the copper may produce airborne contaminants. Consult Sections 3 & 8 for further information.  SECTION 3 — COMPOSITION/INFORMATION ON INGREDIENTS  CHEMICAL NAME  CU  COPPET 7440-50-8 84.7% 2n 2n Zinc 1314-13-2 15.0% Si SECTION 4 — FIRST AID MEASURES  Eye injuries from solid particles should receive immediate medical attention. Dust may be flushed from eyes immediately with large amounts of water, lifting the lower and upper lids occasionally; seek medical attention.  Cuts or abrasions should be treated promptly with thorough cleansing of the affected area. Wash the skin using soap or mild detergent and water. Get medical attention if irritation develops and persists.  If the product or dust is swallowed, seek immediate medical attention or advice. Do rinduce vomiting.  If breathing has stopped, perform artificial respiration and obtain medical aid immediately. If breathing is difficult, provide fresh air and seek medical attention as	OTHER DESIG	NATIONS	5:			
MANUFACTURER'S INFORMATION: NORTH EAST, PA 16428  EMERGENCY PHONE NO.: 814-725-9621 WEBSITE: WWW.ELECMAT.COM  RECOMMENDED USE AND RESTRICTIONS ON USE: Manufacturing & Industry for non-structural components predominantly to conduct electrical current.  SECTION 2 — HAZARD IDENTIFICATION  COPPER and copper alloys are considered on "article" and not hazardous in its solid from. However, certain processes such as cutting, milling, grinding, meltiand welding could result in some hazardous materials being emitted.  Fumes from hot processes may contain other compounds with differe exposure limits. Dust or fumes generated by machining, grinding, welding or thermal cutting of the copper may produce airborne contaminants. Consult Sections 3 & 8 for further information.  SECTION 3 — COMPOSITION/INFORMATION ON INGREDIENTS  CHEMICAL NAME  COMMON NAME  CAS # PERCENT WEIGI  CU  Copper 7440-50-8 84.7%  Zn Zinc 1314-13-2 15.0%  Si Silicon 7440-21-3 0.3%  SECTION 4 — FIRST AID MEASURES  Eye injuries from solid particles should receive immediate medical attention. Dust me be flushed from eyes immediately with large amounts of water, lifting the lower and upper lids occasionally; seek medical attention.  Cuts or abrasions should be treated promptly with thorough cleansing of the affected area. Wash the skin using soap or mild detergent and water. Get medical attention if irritation develops and persists.  If the product or dust is swallowed, seek immediate medical attention or advice. Do reinduce vomiting.  If breathing has stopped, perform artificial respiration and obtain medical aid immediately. If breathing is difficult, provide fresh air and seek medical attention as	PRODUCT IDENTII	ICATION	Copper and Copper Alloys			
RECOMMENDED USE AND RESTRICTIONS ON USE:  Manufacturing & Industry for non-structural components predominantly to conduct electrical current.  SECTION 2 – HAZARD IDENTIFICATION  CLASSIFICATION:  CLASSIFICATION:  CLASSIFICATION:  CLASSIFICATION:  COpper and copper alloys are considered on "article" and not hazardous in its solid from. However, certain processes such as cutting, milling, grinding, meltiand welding could result in some hazardous materials being emitted.  Fumes from hot processes may contain other compounds with differe exposure limits. Dust or fumes generated by machining, grinding, welding or thermal cutting of the copper may produce airborne contaminants. Consult Sections 3 & 8 for further information.  SECTION 3 – COMPOSITION/INFORMATION ON INGREDIENTS  CHEMICAL NAME  CU  COPPER 7440-50-8 84.7%  Zn  Zinc  1314-13-2 15.0%  Si Silicon  7440-21-3 0.3%  SECTION 4 – FIRST AID MEASURES  Eye injuries from solid particles should receive immediate medical attention. Dust may be flushed from eyes immediately with large amounts of water, lifting the lower and upper lids occasionally; seek medical attention.  Cuts or abrasions should be treated promptly with thorough cleansing of the affected area. Wash the skin using soap or mild detergent and water. Get medical attention if irritation develops and persists.  If the product or dust is swallowed, seek immediate medical attention or advice. Do reinduce vomiting.  If breathing has stopped, perform artificial respiration and obtain medical aid immediately. If breathing is difficult, provide fresh air and seek medical attention as	MANUFACTURER'S INFOR	RMATION	N: 50 SOUTH WASHINGTON STREE			
SECTION 2 - HAZARD IDENTIFICATION	EMERGENCY PHONE NO.:		.: 814-725-9621	WEBSITE:	WWW.EL	ECMAT.COM
CLASSIFICATION: CLASSIFICATION				y to conduct e	lectrical c	urrent.
CLASSIFICATION: solid from. However, certain processes such as cutting, milling, grinding, meltiand welding could result in some hazardous materials being emitted.  Fumes from hot processes may contain other compounds with differe exposure limits. Dust or fumes generated by machining, grinding, welding or thermal cutting of the copper may produce airborne contaminants. Consult Sections 3 & 8 for further information.  SECTION 3 – COMPOSITION/INFORMATION ON INGREDIENTS  CHEMICAL NAME  CU  COPPER  TA440-50-8  84.7%  Zn  Zinc  1314-13-2  15.0%  Si Silicon  SECTION 4 – FIRST AID MEASURES  Eye injuries from solid particles should receive immediate medical attention. Dust may be flushed from eyes immediately with large amounts of water, lifting the lower and upper lids occasionally; seek medical attention.  Cuts or abrasions should be treated promptly with thorough cleansing of the affected area. Wash the skin using soap or mild detergent and water. Get medical attention if irritation develops and persists.  INGESTION:  If the product or dust is swallowed, seek immediate medical attention or advice. Do rinduce vomiting.  If breathing has stopped, perform artificial respiration and obtain medical aid immediately. If breathing is difficult, provide fresh air and seek medical attention as			SECTION 2 – HAZARD IDENTIFIC	ATION		
CHEMICAL NAME  CU  COPPET  Type  Typ		CLASSIFICATION: solid from. However, certain processes such as cutting, milling, grinding, me and welding could result in some hazardous materials being emitted.  Fumes from hot processes may contain other compounds with diffe exposure limits. Dust or fumes generated by machining, grinding,				lling, grinding, melting g emitted. Dounds with different lining, grinding,
CHEMICAL NAME  CU Copper 7440-50-8 84.7% Zn Zinc Silicon 7440-21-3 0.3%  SECTION 4 — FIRST AID MEASURES  Eye injuries from solid particles should receive immediate medical attention. Dust may be flushed from eyes immediately with large amounts of water, lifting the lower and upper lids occasionally; seek medical attention.  Cuts or abrasions should be treated promptly with thorough cleansing of the affected area. Wash the skin using soap or mild detergent and water. Get medical attention if irritation develops and persists.  INGESTION:  If the product or dust is swallowed, seek immediate medical attention or advice. Do rinduce vomiting.  If breathing has stopped, perform artificial respiration and obtain medical aid immediately. If breathing is difficult, provide fresh air and seek medical attention as						
Cu Copper 7440-50-8 84.7%  Zn Zinc 1314-13-2 15.0%  Si Silicon 7440-21-3 0.3%  SECTION 4 – FIRST AID MEASURES  Eye injuries from solid particles should receive immediate medical attention. Dust may be flushed from eyes immediately with large amounts of water, lifting the lower and upper lids occasionally; seek medical attention.  Cuts or abrasions should be treated promptly with thorough cleansing of the affected area. Wash the skin using soap or mild detergent and water. Get medical attention if irritation develops and persists.  INGESTION: If the product or dust is swallowed, seek immediate medical attention or advice. Do reinduce vomiting.  If breathing has stopped, perform artificial respiration and obtain medical aid immediately. If breathing is difficult, provide fresh air and seek medical attention as		SECTION	3 – COMPOSITION/INFORMATION	ON INGREDIE	NTS	
Zn Silicon 7440-21-3 0.3%  SECTION 4 – FIRST AID MEASURES  Eye injuries from solid particles should receive immediate medical attention. Dust may be flushed from eyes immediately with large amounts of water, lifting the lower and upper lids occasionally; seek medical attention.  Cuts or abrasions should be treated promptly with thorough cleansing of the affected area. Wash the skin using soap or mild detergent and water. Get medical attention if irritation develops and persists.  INGESTION:  If the product or dust is swallowed, seek immediate medical attention or advice. Do reinduce vomiting.  If breathing has stopped, perform artificial respiration and obtain medical aid immediately. If breathing is difficult, provide fresh air and seek medical attention as	CHEMICAL NAME		COMMON NAME	CAS	#	PERCENT WEIGHT
Eye injuries from solid particles should receive immediate medical attention. Dust may be flushed from eyes immediately with large amounts of water, lifting the lower and upper lids occasionally; seek medical attention.  Cuts or abrasions should be treated promptly with thorough cleansing of the affected area. Wash the skin using soap or mild detergent and water. Get medical attention if irritation develops and persists.  INGESTION:  If the product or dust is swallowed, seek immediate medical attention or advice. Do reinduce vomiting.  If breathing has stopped, perform artificial respiration and obtain medical aid immediately. If breathing is difficult, provide fresh air and seek medical attention as	Zn		Zinc	1314-1	.3-2	15.0%
be flushed from eyes immediately with large amounts of water, lifting the lower and upper lids occasionally; seek medical attention.  Cuts or abrasions should be treated promptly with thorough cleansing of the affected area. Wash the skin using soap or mild detergent and water. Get medical attention if irritation develops and persists.  INGESTION:  INGESTION:  If the product or dust is swallowed, seek immediate medical attention or advice. Do rinduce vomiting.  If breathing has stopped, perform artificial respiration and obtain medical aid immediately. If breathing is difficult, provide fresh air and seek medical attention as			SECTION 4 – FIRST AID MEASU	JRES		
SKIN CONTACT: area. Wash the skin using soap or mild detergent and water. Get medical attention if irritation develops and persists.  INGESTION: If the product or dust is swallowed, seek immediate medical attention or advice. Do rinduce vomiting.  If breathing has stopped, perform artificial respiration and obtain medical aid immediately. If breathing is difficult, provide fresh air and seek medical attention as	EYE CONTACT:	, , , , , , , , , , , , , , , , , , , ,				
induce vomiting.  If breathing has stopped, perform artificial respiration and obtain medical aid immediately. If breathing is difficult, provide fresh air and seek medical attention as	SKIN CONTACT:	Cuts or abrasions should be treated promptly with thorough cleansing of the affected area. Wash the skin using soap or mild detergent and water. Get medical attention if				
INHALATION: immediately. If breathing is difficult, provide fresh air and seek medical attention as	INGESTION:	If the p	f the product or dust is swallowed, seek immediate medical attention or advice. Do not			
ουστι αο μυσοιωία.	INHALATION:					

	SEC	CTION	I 5 – FIREFIGHTING MEASURES		
FLAMMABLE F			applicable		
EXTINGUISHING MEDIA: Not applicable; non-combustible					
For a dust fire in a confined area, use a respirator approved for toxic du				or approved for toxic dusts	
			fumes. Do not use water to extinguish fires	• •	
PROTECTION OF FIR	REFIGHTERS:		lving molten metal due to the potential for	•	
TROTECTION OF TH			- ACCIDENTAL RELEASE MEASURES	эссин схртозгона.	
	320		7.66.5		
Clean-Up Procedures: Produ	ct in solid for	m may	y be picked up by hand or other means to b	e placed into a container.	
•			e the dispersion of dust such as a high efficient	•	
_			covered material in a suitable, covered, and		
,					
	SEC	CTION	7 – HANDLING AND STORAGE		
DECOMMENDE	D STODAGE	Mair	ntain good housekeeping to prevent exposu	re to materials and	
RECOMMENDE	D STORAGE:	chen	nicals that may contaminate or impair the c	quality of the product.	
		This	product does not require special safety pre	cautions for the handling	
		prior	to installation. Installation and removal of	the product may cause	
PROCEDURES FOR	HANDLING	expo	sure to dusts and other materials or chemi-	cals associated with the	
PROCEDURES FOR	HANDLING.	insta	Illation (work) environment. Operations su	ch as grinding, cutting,	
		burn	ing, and welding may generate dusts or fun	nes which may require	
		spec	ial handling procedures.		
:	SECTION 8 – E	XPOS	SURE CONTROLS/PERSONAL PROTECTION		
	When mach	ining,	heating, or melting, use adequate local (pr	eferably) or general	
	exhaust ven	xhaust ventilation to ensure that concentrations of dusts or fumes do not exceed			
ENGINEERING CONTROLS:	exposure limits. Keep workplace clean and dry (unless wet machining is being used to				
capture dust and fume). Train personnel to minimize exposure					
			·	_	
	installation	and re	eplacement of product. On a regular basis,	_	
	installation	and re	eplacement of product. On a regular basis, ment in which the product will be installed.	verify condition and proper	
SUBSTANCI	installation a function of e	and re	eplacement of product. On a regular basis, ment in which the product will be installed.  ACGIH TLV	verify condition and proper	
SUBSTANCI	installation a function of e	and re	eplacement of product. On a regular basis, ment in which the product will be installed.	verify condition and proper  OSHA PEL  mg/m³	
<b>SUBSTANCI</b> Cu	installation a function of e	and re	eplacement of product. On a regular basis, ment in which the product will be installed.  ACGIH TLV  mg/m³  1	OSHA PEL mg/m <sup>3</sup> 1 (dust)	
Cu	installation a function of e	and re	eplacement of product. On a regular basis, ment in which the product will be installed.  ACGIH TLV  mg/m³  1  0.2	verify condition and proper  OSHA PEL  mg/m³	
Cu Zn	installation a function of e	and re	eplacement of product. On a regular basis, ment in which the product will be installed.  ACGIH TLV  mg/m³  1  0.2  5	OSHA PEL mg/m³ 1 (dust) 0.2 (fume)	
Cu Zn Si	installation a function of e	and re	eplacement of product. On a regular basis, ment in which the product will be installed.  ACGIH TLV mg/m³  1 0.2 5 10	OSHA PEL mg/m³ 1 (dust) 0.2 (fume) 5 10	
Cu Zn Si <b>SUPPLEMENTAL INFORMATI</b>	installation a function of e	and re	eplacement of product. On a regular basis, ment in which the product will be installed.  ACGIH TLV  mg/m³  1  0.2  5  10  SUPPLEMENTAL INFORMATION	OSHA PEL mg/m³  1 (dust) 0.2 (fume) 5 10  SUPPLEMENTAL	
Cu Zn Si <b>SUPPLEMENTAL INFORMATI</b> Individual protection measur	installation of the function o	and re	ACGIH TLV mg/m³  1 0.2 5 10  SUPPLEMENTAL INFORMATION Individual protection measures: Use an	OSHA PEL mg/m³  1 (dust) 0.2 (fume) 5 10  SUPPLEMENTAL INFORMATION	
Cu Zn Si SUPPLEMENTAL INFORMATI Individual protection measur appropriate gloves to protect	installation of function of of the function	and reequip	ACGIH TLV mg/m³  1 0.2 5 10  SUPPLEMENTAL INFORMATION Individual protection measures: Use an approved respirator, with the product. On a regular basis, ment in which the proper	OSHA PEL mg/m³ 1 (dust) 0.2 (fume) 5 10 SUPPLEMENTAL INFORMATION Individual protection:	
Cu Zn Si SUPPLEMENTAL INFORMATI Individual protection measur appropriate gloves to protect hazards. Always wear safety	installation a function of of the function of of the function of of the function of of the function of the fun	ical	ACGIH TLV mg/m³  1 0.2 5 10  SUPPLEMENTAL INFORMATION Individual protection measures: Use an approved respirator, with the proper assigned protection factor, whenever	OSHA PEL mg/m³ 1 (dust) 0.2 (fume) 5 10 SUPPLEMENTAL INFORMATION Individual protection: Workers should was	
Cu Zn Si SUPPLEMENTAL INFORMATI Individual protection measur appropriate gloves to protect hazards. Always wear safety shields and appropriate hear	installation a function of of the function of of the function of of the function of of the function of the fun	ical	ACGIH TLV mg/m³  1 0.2 5 10  SUPPLEMENTAL INFORMATION Individual protection measures: Use an approved respirator, with the proper assigned protection factor, whenever airborne concentrations of hazardous	OSHA PEL mg/m³  1 (dust) 0.2 (fume) 5 10  SUPPLEMENTAL INFORMATION Individual protection: Workers should was before meals and leaving	
Cu Zn Si SUPPLEMENTAL INFORMATI Individual protection measur appropriate gloves to protect hazards. Always wear safety shields and appropriate hear	installation a function of of the function of of the function of of the function of of the function of the fun	ical	ACGIH TLV mg/m³  1 0.2 5 10  SUPPLEMENTAL INFORMATION Individual protection measures: Use an approved respirator, with the proper assigned protection factor, whenever airborne concentrations of hazardous components exceed exposure limits	OSHA PEL mg/m³ 1 (dust) 0.2 (fume) 5 10 SUPPLEMENTAL INFORMATION Individual protection: Workers should was	
Zn Si  SUPPLEMENTAL INFORMATI Individual protection measur appropriate gloves to protect hazards. Always wear safety shields and appropriate hear when grinding or cutting.	installation of function of of function of of the function of of the function	ical	ACGIH TLV mg/m³  1 0.2 5 10  SUPPLEMENTAL INFORMATION Individual protection measures: Use an approved respirator, with the proper assigned protection factor, whenever airborne concentrations of hazardous components exceed exposure limits listed above.	OSHA PEL mg/m³  1 (dust) 0.2 (fume) 5 10  SUPPLEMENTAL INFORMATION Individual protection: Workers should was before meals and leaving work.	
Cu Zn Si  SUPPLEMENTAL INFORMATI Individual protection measur appropriate gloves to protect hazards. Always wear safety shields and appropriate hear when grinding or cutting.  TERMS: ALL EXPOSURE LIMI	installation of function of of function of of the function of of the function	ical	ACGIH TLV mg/m³  1 0.2 5 10  SUPPLEMENTAL INFORMATION Individual protection measures: Use an approved respirator, with the proper assigned protection factor, whenever airborne concentrations of hazardous components exceed exposure limits	OSHA PEL mg/m³  1 (dust) 0.2 (fume) 5 10  SUPPLEMENTAL INFORMATION Individual protection: Workers should was before meals and leaving work.	
Cu Zn Si  SUPPLEMENTAL INFORMATI Individual protection measur appropriate gloves to protect hazards. Always wear safety shields and appropriate hear when grinding or cutting.  TERMS: ALL EXPOSURE LIMIT OTHERWISE NOTED.	on es: Use t against phys glasses with s ing protection	ical side	ACGIH TLV mg/m³  1 0.2 5 10  SUPPLEMENTAL INFORMATION Individual protection measures: Use an approved respirator, with the proper assigned protection factor, whenever airborne concentrations of hazardous components exceed exposure limits listed above.  REIN ARE 8 HOUR TIMEWEIGHTED AVERAGE	OSHA PEL mg/m³  1 (dust) 0.2 (fume) 5 10  SUPPLEMENTAL INFORMATION Individual protection: Workers should was before meals and leaving work.  ES (TWA) UNLESS	
Cu  Zn Si  SUPPLEMENTAL INFORMATI Individual protection measur appropriate gloves to protect hazards. Always wear safety shields and appropriate hear when grinding or cutting.  TERMS: ALL EXPOSURE LIMITOTHERWISE NOTED.	installation of function of fu	ical side	ACGIH TLV mg/m³  1 0.2 5 10  SUPPLEMENTAL INFORMATION Individual protection measures: Use an approved respirator, with the proper assigned protection factor, whenever airborne concentrations of hazardous components exceed exposure limits listed above.	OSHA PEL mg/m³  1 (dust) 0.2 (fume) 5 10  SUPPLEMENTAL INFORMATION Individual protection: Workers should was before meals and leaving work.  ES (TWA) UNLESS	
Cu  Zn Si  SUPPLEMENTAL INFORMATI Individual protection measur appropriate gloves to protect hazards. Always wear safety shields and appropriate hear when grinding or cutting.  TERMS: ALL EXPOSURE LIMIT OTHERWISE NOTED. TLV = THRESHOLD LIMIT VAL	on es: Use t against phys glasses with s ing protection TS REFERENCE UE/AMERICAL JBIC METER	ical side	ACGIH TLV mg/m³  1 0.2 5 10  SUPPLEMENTAL INFORMATION Individual protection measures: Use an approved respirator, with the proper assigned protection factor, whenever airborne concentrations of hazardous components exceed exposure limits listed above.  REIN ARE 8 HOUR TIMEWEIGHTED AVERAGE	OSHA PEL mg/m³ 1 (dust) 0.2 (fume) 5 10 SUPPLEMENTAL INFORMATION Individual protection: Workers should was before meals and leaving work. ES (TWA) UNLESS	

APPEARANCE/PHYSICAL STATE: Metallic solid with a copper color

ODOR/ODOR THRESHOLD:	VAPOR DENSITY:
None	Not volatile
MELTING/FREEZING POINT:	SPECIFIC GRAVITY: (relative density)
Approximately 1035°C (1880°F) for copper	8.75 g/cm <sup>3</sup> (0.32 lb./in <sup>3</sup> ) for copper (water = 1)
BOILING POINT:	VAPOR PRESSURE:
2500°C (4530°F) for copper	~ 0 mm/Hg
FLASH POINT:	EVAPORATION RATE:
Not determined	Not volatile
FLAMMABILITY:	SOLUBILITY IN WATER:
Not flammable	Insoluble
UPPER & LOWER FLAMMABILITY LIMITS:	pH:
Not applicable	Not applicable
AUTO IGNITION TEMPERATURE:	VISCOSITY:
Not applicable	Not applicable
DECOMPOSITION TEMPERATURE:	PARTITION COEFFICIENT:
Not applicable	Not applicable

	SECTION 10 – STABILITY & REAC	TIVITY		
CHEMICAL STABILITY:				
Stable under normal use con	ditions			
CONDITIONS TO AVOID:				
Temperatures > 150° C (300° F), which may soften the copper material.				
REACTIVITY:		INCOMPATIBLE MATERIALS:		
Copper may react with acetylene gas to form copper acetylides, which		Dust is explosively incompatible with		
	er may react with strong acids to generate	sodium azide.		
explosive gas (e.g. hydrogen).				
HAZARDOUS DECOMPOSITIO	N PRODUCTS:	HAZARDOUS POLYMERIZATION:		
None		The melting of this product may release		
		metal oxides.		
	SECTION 11 – TOXICOLOGICAL INFO			
	: Symptoms related to the physical, chemic			
Under normal handling and use, exposure to product presents few health hazards. Dusts may cause mechanical				
irritations to eyes and skin. Ingestion may cause transient irritation of throat, stomach and gastrointestinal tract.				
,	<u> </u>	Higher dust exposures may cause difficulty		
breathing, congestion, and chest tightness.				
EYE CONTACT:		ition, discoloration, and damage. As a foreign		
	body in the lens, copper dust may cause a dense cataract and discolor the lens.			
SKIN:	Copper can cause some irritation with possible discoloration of skin.			
Ingestion of significant amounts of welding electrodes is unlikely. If copper is				
INGESTION:	swallowed and person is conscious, give large quantities of water to drink. Get medical			
	attention as soon as possible. Serious effects may occur if large amounts of dust are			
swallowed.				
	Breathing metal dust may worsen symptoms of individuals with pre-existing chronic			
respiratory disease. Follow exposure guidelines for copper dust and fume. Acute				
INHALATION:	INHALATION: exposure to dust or fume may cause upper respiratory tract irritation, metallic taste in			
mouth, nausea, fatigue, and/or metal fume fever. Breathing copper dust may worsen				
symptoms of individuals with pre-existing chronic respiratory disease.  Carcinogen Classification of Ingredients				
Page 3 of 6				

Ingredient	OSHA	NTP	IARC	Target Organ
None				

#### **TERMS:**

OSHA – Occupational Safety & Health Administration

Y = Listed as a human carcinogen

NTP - National Toxicology Program

K = Known to be a human carcinogen

R = Reasonably anticipated to be a human carcinogen (RAHC)

IARC - International Agency for Research on Cancer

1 = Carcinogenic to humans

2A = Probably carcinogenic to humans

2B = Possibly carcinogenic to humans

3 = Unclassifiable as to carcinogenicity to humans

4 = Probably not carcinogenic to humans

Other -

NL = Not listed

SECTION 12 – ECOLOGICAL INFORMATION			
ECOTOXICITY	PERSISTENCE AND DEGRADABILITY		
Not applicable	Not applicable		
BIOACCUMULATION POTENTIAL	MOBILITY IN SOIL		
Not applicable	Not applicable		

#### OTHER ADVERSE EFFECTS

Copper metal is relatively insoluble in water and, therefore, generally has low bioavailability. This product is not expected to present an environmental hazard. Avoid releasing dusts and fumes into the environment.

# **SECTION 13 – DISPOSAL CONSIDERATIONS**

Recover or Recycle if possible. Dispose of according to Federal, State and Local Regulations. Dust collected from machining, welding, etc. may be classified as a hazardous waste. Consult Federal, State and Local regulations.

SECTION 14 – TRANSPORT INFORMATION				
US DEPT OF TRANSPORTATION	CANADIAN TRANSPORTATION OF			
(DOT)-HMR (Hazardous Materials Registration)	DANGEROUS GOODS (TDG)			
Not regulated	Not regulated			
UN SHIPPING NAME	UN NUMBER			
Not regulated	Not regulated			
TRANSPORT HAZARD CLASS	PACKING GROUP			
Not regulated	Not regulated			
ENVIRONMENTAL HAZARDS	LABEL(S) REQUIRED?			
None	No			
TRANSPORT IN BULK	SPECIAL SHIPPING INFORMATION			
Not applicable	Not applicable			
SECTION 15 - REGULATORY INFORMATION				

**US-OSHA (HAZARD COMMUNICATION STANDARD)** 

References

SARA TITLE III SECTION 302 (40CFR 355), SARA TITLE III 311/312 (40 CFR 370), SARA TITLE III 313 (40 CFR 372)

Component	CAS#	% By Weight
Copper	7440-50-8	≥ 84.7
Zinc	1314.13-2	≥ 15.0
Silicon	7440-21-3	≥ 0.3

# US-EPA (TOXIC SUBSTANCES CONTROL ACT - TSCA)

All components of these products are on the TSCA inventory list or are excluded from listing.

**US-EPA (SARA TITLE III)** 

Releases to the environment of **Copper** may be subject to reporting under Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

#### CANADA-WHMIS (WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM)

This SDS has been prepared according to the hazard criteria of the Controlled Product Regulations (CPR) and the SDS contains the information required by the CPR.

### CANADA DSL (DOMESTIC SUSTANCES LIST) INVENTORY STATUS

All components of these products are on the DSL Inventory.

## CEPA (CANDIAN ENVIRONMENTAL PROTECTION ACT)

No components are on the Toxic Substances List.

# EINECS NO. (EUROPEAN INVENTORY OF EXISTING COMMERCIAL CHEMICAL SUBSTANCES)

All components of these products are on the EINECS list.

# RoHS (RESTRICTION OF CERTAIN HAZARDOUS SUBSTANCES) COMPLIANCE

Castings comply with RoHS.

### CALIFORNIA PROPOSITION 65 COMPLIANCE

Copper is not on California's Proposition 65 list. (California Health & Safety Code 25248.5 et seq.)

#### US STATE REGULATORY INFORMATION

Some of the components listed I Section 3 (e.g., Copper) may be covered under specific state regulations.

# **SECTION 16 – OTHER INFORMATION**

## SDS PREPARED BY

The information herein is given in good faith and based on technical date The Electric Materials Company believes to be reliable. Since the conditions of use are outside our control, we assume no liability in connection with any use of this information and no warranty, expressed or implied is given. Contact the Electric Materials Company or its associates for additional information.

DATE 05/2015

# NOTE:

This data and label information is offered in good faith as typical values and not as a product specification. No warranty either expressed or implied is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally acceptable. However, each user should review the recommendations in specific context of the intended use and determine if they are appropriate.

LABEL Information:

We have no current labels for C23030.