THE ELECTRIC MATE	RIALS		SAFET	Y DATA	SHEET (SDS)	
COMMUTATORS-EXTRUSIONS-ROTOR BAR-CASTINGS-FORGINGS				ID: <b>C230</b>	30	
			DATE ISSU	ED: <b>5/28</b>	/2015	
SEC	TION 1	- PRODUCT IDENTIFICATION & COM	IPANY INFOR	MATION		
PRODUC	CT NAM	E: C23030 MODIFIED RED BRASS N	C23030 MODIFIED RED BRASS METAL COPPER ALLOY			
OTHER DESIG	NATION	IS:				
PRODUCT IDENTIFICATION:		N: Copper and Copper Alloys	Copper and Copper Alloys			
MANUFACTURER'S INFORMATION:			THE ELECTRIC MATERIALS COMPANY 50 SOUTH WASHINGTON STREET NORTH EAST, PA 16428			
EMERGENCY PH	ONE NO	D.: <b>814-725-9621</b>	WEBSITE:	WWW.ELE	CMAT.COM	
RECOMMENDED USE AND RESTRICTIONS ON USE: Manufacturing & Industry for non-structural components predominantly to conduct electrical current.				irrent.		
		SECTION 2 – HAZARD IDENTIFIC	ATION			
CLASSIFICATION: so		copper and copper alloys are considered on "article" and not hazardous in its olid from. However, certain processes such as cutting, milling, grinding, melting nd welding could result in some hazardous materials being emitted.				
OTHER INFORMATION:		Fumes from hot processes may contain other compounds with different exposure limits. Dust or fumes generated by machining, grinding, welding or thermal cutting of the copper may produce airborne contaminants. Consult Sections 3 & 8 for further information.				
	SECTIO	N 3 – COMPOSITION/INFORMATION				
CHEMICAL NAME		COMMON NAME	CAS	;#	PERCENT WEIGHT	
Cu Zn Si		Copper Zinc Silicon	7440- 1314- 7440-	13-2	84.7% 15.0% 0.3%	
		SECTION 4 – FIRST AID MEASU	JRES			
EYE CONTACT:	Eye injuries from solid particles should receive immediate medical attention. Dust may be flushed from eyes immediately with large amounts of water, lifting the lower and upper lids occasionally; seek medical attention.					
SKIN CONTACT:	Cuts or abrasions should be treated promptly with thorough cleansing of the affected area. Wash the skin using soap or mild detergent and water. Get medical attention if irritation develops and persists.					
INGESTION:	If the product or dust is swallowed, seek immediate medical attention or advice. Do not induce vomiting.					
INHALATION:	If breathing has stopped, perform artificial respiration and obtain medical aid immediately. If breathing is difficult, provide fresh air and seek medical attention as soon as possible.					
	I					

SECTION 5 – FIREFIGHTING MEASURES					
FLAMMABLE PROPERTIES:			applicable		
		ot applicable; non-combustible			
		For a	dust fire in a confined area, use a respirate	or approved for toxic dusts	
			fumes. Do not use water to extinguish fires	around operations	
PROTECTION OF FIR			ving molten metal due to the potential for	steam explosions.	
	SECTIC	DN 6 -	ACCIDENTAL RELEASE MEASURES		
When cleaning dust, use met	hods that mir et clean-up. F	nimize Put re	y be picked up by hand or other means to b the dispersion of dust such as a high efficience covered material in a suitable, covered, and	ency particulate air (HEPA)	
	SEC		I 7 – HANDLING AND STORAGE		
RECOMMENDE	O STORAGE:	chen	ntain good housekeeping to prevent exposunicals that may contaminate or impair the c	uality of the product.	
			product does not require special safety pre	-	
		•	to installation. Installation and removal of		
PROCEDURES FOR	HANDLING:	•	sure to dusts and other materials or chemi		
			Illation (work) environment. Operations su		
			ing, and welding may generate dusts or fur	nes which may require	
			special handling procedures. XPOSURE CONTROLS/PERSONAL PROTECTION		
				eferably) or general	
		-	ing, heating, or melting, use adequate local (preferably) or general lation to ensure that concentrations of dusts or fumes do not exceed		
		limits. Keep workplace clean and dry (unless wet machining is being used to			
ENGINEERING CONTROLS:	•	ust and fume). Train personnel to minimize exposure to hazards during			
		and replacement of product. On a regular basis, verify condition and proper			
	function of e	equip	ment in which the product will be installed.		
SUBSTANCE			ACGIH TLV	OSHA PEL	
	-		mg/m <sup>3</sup>	mg/m <sup>3</sup>	
Cu			1	1 (dust)	
7.			0.2	0.2 (fume)	
Zn Si			5	5	
			10 SUPPLEMENTAL INFORMATION	10 SUPPLEMENTAL	
Individual protection measures: Use			Individual protection measures: Use an	INFORMATION	
appropriate gloves to protect		ical	approved respirator, with the proper	Individual protection:	
hazards. Always wear safety glasses with side			assigned protection factor, whenever	Workers should was	
shields and appropriate heari	•		airborne concentrations of hazardous	before meals and leaving	
when grinding or cutting.			components exceed exposure limits	work.	
			listed above.		
<b>TERMS:</b> ALL EXPOSURE LIMITS REFERENCED HEREIN ARE 8 HOUR TIMEWEIGHTED AVERAGES (TWA) UNLESS OTHERWISE NOTED.					
TLV = THRESHOLD LIMIT VALUE/AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS (ACGIH) mg/m <sup>3</sup> = MILLIGRAMS PER CUBIC METER					
PERSONAL PROTECTION:	Proper hand and foot protection is recommended				
SECTION 9 – PHYSICAL & CHEMICAL PROPERTIES					
APPEARANCE/PHYSICAL STATE:					
Metallic solid with a copper color					
Dage 2 of 6					

ODOR/ODOR THRESHOLD:	VAPOR DENSITY:
None	Not volatile
MELTING/FREEZING POINT:	SPECIFIC GRAVITY: (relative density)
Approximately 1035°C (1880°F) for copper	$8.75 \text{ g/cm}^3$ (0.32 lb./in <sup>3</sup> ) for copper (water = 1)
BOILING POINT:	VAPOR PRESSURE:
2500°C (4530°F) for copper	~ 0 mm/Hg
FLASH POINT:	EVAPORATION RATE:
Not determined	Not volatile
FLAMMABILITY:	SOLUBILITY IN WATER:
Not flammable	Insoluble
UPPER & LOWER FLAMMABILITY LIMITS:	pH:
Not applicable	Not applicable
AUTO IGNITION TEMPERATURE:	VISCOSITY:
Not applicable	Not applicable
DECOMPOSITION TEMPERATURE:	PARTITION COEFFICIENT:
Not applicable	Not applicable

SECTION 10 – STABILITY & REACTIVITY				
CHEMICAL STABILITY:				
Stable under normal use conditions				
CONDITIONS TO AVOID:				
Temperatures > 150° C (300° F), which may soften the copper material.				
REACTIVITY:		INCOMPATIBLE MATERIALS:		
Copper may react with acety	lene gas to form copper acetylides, which	Dust is explosively incompatible with		
are sensitive to shock. Coppe	er may react with strong acids to generate	sodium azide.		
explosive gas (e.g. hydrogen)				
HAZARDOUS DECOMPOSITIC	IN PRODUCTS:	HAZARDOUS POLYMERIZATION:		
None		The melting of this product may release		
		metal oxides.		
SECTION 11 – TOXICOLOGICAL INFORMATION				
POTENTIAL HEALTH EFFECTS: Symptoms related to the physical, chemical and toxicological characteristics				
Under normal handling and u	use, exposure to product presents few healt	h hazards. Dusts may cause mechanical		
irritations to eyes and skin. I	ngestion may cause transient irritation of th	nroat, stomach and gastrointestinal tract.		
Inhalation may cause coughing, nose and throat irritation, and sneezing. Higher dust exposures may cause difficulty				
breathing, congestion, and chest tightness.				
EYE CONTACT:	If present as dust, copper may cause irritation, discoloration, and damage. As a foreign			
	body in the lens, copper dust may cause a dense cataract and discolor the lens.			
SKIN:	Copper can cause some irritation with possible discoloration of skin.			
	Ingestion of significant amounts of welding electrodes is unlikely. If copper is			
INGESTION:	swallowed and person is conscious, give large quantities of water to drink. Get medical			
indestion.	attention as soon as possible. Serious effects may occur if large amounts of dust are			
swallowed.				
	Breathing metal dust may worsen symptoms of individuals with pre-existing chronic			
	respiratory disease. Follow exposure guidelines for copper dust and fume. Acute			
INHALATION:	exposure to dust or fume may cause upper respiratory tract irritation, metallic taste in			
	mouth, nausea, fatigue, and/or metal fume fever. Breathing copper dust may worsen			
symptoms of individuals with pre-existing chronic respiratory disease.				
Carcinogen Classification of Ingredients				

Ingredient	OSHA	NTP	IARC	Target Orgar
None				
TERMS:				
OSHA – Occupational Safety & Health Administrati	on			
Y = Listed as a human carcinogen				
NTP – National Toxicology Program				
K = Known to be a human carcinogen				
R = Reasonably anticipated to be a human carci	nogen (RAHC)			
IARC – International Agency for Research on Cance	er			
1 = Carcinogenic to humans				
2A = Probably carcinogenic to humans				
2B = Possibly carcinogenic to humans				
3 = Unclassifiable as to carcinogenicity to human	ns			
4 = Probably not carcinogenic to humans				
Other –				
NL = Not listed				
SECTION 12	- ECOLOGICAL	INFORMATIO	ON	
ECOTOXICITY		PERS	ISTENCE AND	DEGRADABILITY
Not applicable			Not applicable	
BIOACCUMULATION POTENTIAL MOBILITY IN SOIL				
Not applicable Not applicable				
OTHER ADVERSE EFFECTS				

Copper metal is relatively insoluble in water and, therefore, generally has low bioavailability. This product is not expected to present an environmental hazard. Avoid releasing dusts and fumes into the environment.

## SECTION 13 – DISPOSAL CONSIDERATIONS

Recover or Recycle if possible. Dispose of according to Federal, State and Local Regulations. Dust collected from machining, welding, etc. may be classified as a hazardous waste. Consult Federal, State and Local regulations.

SECTION 14 – TRANSPORT INFORMATION				
US DEPT OF TRANSPORTATION	CANADIAN TRANSPORTATION OF			
(DOT)-HMR (Hazardous Materials Registration)	DANGEROUS GOODS (TDG)			
Not regulated	Not regulated			
UN SHIPPING NAME	UN NUMBER			
Not regulated	Not regulated			
TRANSPORT HAZARD CLASS	PACKING GROUP			
Not regulated	Not regulated			
ENVIRONMENTAL HAZARDS	LABEL(S) REQUIRED?			
None	No			
TRANSPORT IN BULK	SPECIAL SHIPPING INFORMATION			
Not applicable	Not applicable			
SECTION 15 - REGULATORY INFORMATION				

US-OSHA (HAZARD C	OMMUNICATI	ON STANDARD)		
References				
	N 302 (40CFR	355), SARA TITLE III 311/312 (40 CFR	370), SARA TITLE III 313 (40 CFR 372)	
	·	<i>"</i>	<i>"</i>	
Component	CAS #	# % By Weight		
Copper		7440-50-8 ≥ 84.7		
Zinc	1314.13-2			
Silicon	7440-21-3	≥ 0.3		
US-EPA (TOXIC SUBS				
	•	are on the TSCA inventory list or are o	excluded from listing.	
US-EPA (SARA TITLE I		men may be subject to reporting up	dar Castion 212 of Title III of the Superfund	
		Act of 1986 and 40 CFR Part 372.	der Section 313 of Title III of the Superfund	
		ZARDOUS MATERIALS INFORMATION	I SYSTEM)	
•			rolled Product Regulations (CPR) and the SDS	
contains the informa	-	-	Tolled Floddet Regulations (CFR) and the 3D3	
	•	ES LIST) INVENTORY STATUS		
•		are on the DSL Inventory.		
CEPA (CANDIAN ENV	IRONMENTAL	PROTECTION ACT)		
No components are o		•		
·				
EINECS NO. (EUROPEAN INVENTORY OF EXISTING COMMERCIAL CHEMICAL SUBSTANCES)				
All components of these products are on the EINECS list.				
RoHS (RESTRICTION OF CERTAIN HAZARDOUS SUBSTANCES) COMPLIANCE				
Castings comply with	RoHS.			
CALIFORNIA PROPOS				
Copper is not on California's Proposition 65 list. (California Health & Safety Code 25248.5 et seq.)				
		1011		
US STATE REGULATO			d under chasific state regulations	
Some of the components listed I Section 3 (e.g., Copper) may be covered under specific state regulations.				
SECTION 16 – OTHER INFORMATION				
SDS PREPARED BY DATE				
The information herein is given in good faith and based on technical 05/2015				
date The Electric Materials Company believes to be reliable. Since the				
conditions of use are	outside our co	ontrol, we assume no liability in		
connection with any	use of this info	ormation and no warranty,		
expressed or implied	is given. Cont	act the Electric Materials Company		
or its associates for a	dditional infor	mation.		
NOTE				
NOTE:				
			and not as a product specification. No	
• •		-	ed industrial hygiene and safe handling	
procedures are believed to be generally acceptable. However, each user should review the recommendations in specific context of the intended use and determine if they are appropriate.				

LABEL Information:

specific context of the intended use and determine if they are appropriate.

We have no current labels for C23030.