THE ELECTRIC MATE			SAFET	'Y DA	TA SHEET (SDS)	
COMMUTATORS-EXTRUSIONS-ROTOR BAR-GASTINGS-FORGINGS				ID: C	308	
			DATE ISSU	ED: 5	5/29/2015	
SEC	TION 1 -	- PRODUCT IDENTIFICATION & COM	PANY INFOR	MATIC	)N	
PRODU	CT NAM	E: C308 TIN BRONZE	C308 TIN BRONZE			
OTHER DESIG	NATION					
PRODUCT IDENTIF		N/A				
MANUFACTURER'S INFORMATION: THE ELECTRIC MATERIA 50 SOUTH WASHINGTO NORTH EAST, PA 16428						
EMERGENCY PH	ONE NO	.: 814-725-9621	WEBSITE:	www	V.ELECMAT.COM	
RECOMMENDED USE AND R Various Castings and Termir		IONS ON USE:				
		SECTION 2 – HAZARD IDENTIFIC	ATION			
CLASSIFIC/	ATION:	Industrial Copper Castings are meta their original form.	llic articles th	nat do r	not present hazards in	
OTHER INFORMA	ATION:	Grinding castings that have not bee may generate significant amounts of Fumes from hot processes may con exposure limits. Dust or fumes gen thermal cutting of the casting may p Sections 3 & 8 for further information	f dust contai tain other co erated by ma produce airbo	ning cr mpoun Ichining	ystalline silica. Ids with different g, grinding, welding or	
	SECTION	I 3 – COMPOSITION/INFORMATION		ENTS		
CHEMICAL NAME			CAS	5#	PERCENT WEIGHT	
Cu	Cu		7440-	50-8	90.0%	
Sn	Sn		7440-		5.0%	
Zn		Zinc	1314-	13-2	5.0%	
SECTION 4 – FIRST AID MEASURES						
EYE CONTACT:	Eye injuries from solid particles should receive immediate medical attention. Dust may be flushed from eyes immediately with large amounts of water, lifting the lower and upper lids occasionally; seek medical attention.					
SKIN CONTACT:	Cuts or abrasions should be treated promptly with thorough cleansing of the affected area. Wash the skin using soap or mild detergent and water. Get medical attention if irritation develops and persists.					
INGESTION:	If the product or dust is swallowed, seek immediate medical attention or advice. Do not induce vomiting.					

INHALATION:	If breathing has stopped, perform artificial respiration and obtain medical aid INHALATION: immediately. If breathing is difficult, provide fresh air and seek medical attention as soon as possible.				
SECTION 5 – FIREFIGHTING MEASURES					
FLAMMABLE I	PROPERTIES:	Not	applicable		
	ING MEDIA:		applicable; non-combustible		
			a dust fire in a confined area, use a respirator approved for toxic dusts		
			fumes. Do not use water to extinguish fires around operations		
PROTECTION OF FI	REFIGHTERS:		lving molten metal due to the potential for	•	
			ACCIDENTAL RELEASE MEASURES	ľ	
When cleaning dust, use me	thods that miner thods that miner the set of	nimize Put re	y be picked up by hand or other means to b the dispersion of dust such as a high efficie covered material in a suitable, covered, and	ency particulate air (HEPA)	
	SE		I 7 – HANDLING AND STORAGE		
RECOMMENDE	D STORAGE:		ntain good housekeeping to prevent exposu		
			nicals that may contaminate or impair the c		
			product does not require special safety pre		
			to installation. Installation and removal of		
PROCEDURES FOR	HANDLING:		posure to dusts and other materials or chemicals associated with the		
			stallation (work) environment. Operations such as grinding, cutting, urning, and welding may generate dusts or fumes which may require		
			ial handling procedures.	nes which may require	
	SECTION 8 - I		SURE CONTROLS/PERSONAL PROTECTION		
When machining, heating, or melting, use adequate local (preferably) or general					
		-	on to ensure that concentrations of dusts or		
			Keep workplace clean and dry (unless wet n		
ENGINEERING CONTROLS:			d fume). Train personnel to minimize exposure to hazards during		
			eplacement of product. On a regular basis,		
	function of equipment in which the product will be installed.				
CURSTANC	Г		ACGIH TLV	OSHA PEL	
SUBSTANC	E		mg/m <sup>3</sup>	mg/m <sup>3</sup>	
Cu			1	1 (dust)	
			0.2	0.2 (fume)	
Sn		2	2		
Zn		5	5		
SUPPLEMENTAL INFORMATION		SUPPLEMENTAL INFORMATION	SUPPLEMENTAL		
Individual protection measures: Use		Individual protection measures: Use an	INFORMATION		
appropriate gloves to protect against physical			approved respirator, with the proper	Individual protection:	
hazards. Always wear safety glasses with side			assigned protection factor, whenever	Workers should was	
shields and appropriate hearing protection			airborne concentrations of hazardous	before meals and leaving	
when grinding or cutting.		components exceed exposure limits listed above.	work.		

## **TERMS:** ALL EXPOSURE LIMITS REFERENCED HEREIN ARE 8 HOUR TIMEWEIGHTED AVERAGES (TWA) UNLESS OTHERWISE NOTED.

TLV = THRESHOLD LIMIT VALUE/AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS (ACGIH)
mg/m <sup>3</sup> = MILLIGRAMS PER CUBIC METER

PERSONAL PROTECTION: Proper hand and foot protection is recommended					
SECTION 9 – PHYSICAL & CHEMICAL PROPERTIES					
APPEARANCE/PHYSICAL STATE:					
Metallic solid with a copper c	color				
ODOR/ODOR THRESHOLD:		VAPOR DENSITY:			
None		Not volatile			
MELTING/FREEZING POINT:		SPECIFIC GRAVITY: (relative density)			
Approximately 1083°C (1980	°F) for copper	$8.9 \text{ g/cm}^3$ (0.32 lb./in <sup>3</sup> ) for copper (water = 1)			
BOILING POINT:		VAPOR PRESSURE:			
2500°C (4530°F) for copper		~ 0 mm/Hg			
FLASH POINT:		EVAPORATION RATE:			
Not determined		Not volatile			
FLAMMABILITY:		SOLUBILITY IN WATER:			
Not flammable		Insoluble			
UPPER & LOWER FLAMMABILITY LIMITS:		pH:			
Not applicable		Not applicable			
AUTO IGNITION TEMPERATURE:		VISCOSITY:			
Not applicable		Not applicable			
DECOMPOSITION TEMPERATURE:		PARTITION COEFFICIENT:			
Not applicable		Not applicable			

SECTION 10 – STABILITY & REACTIVITY					
CHEMICAL STABILITY:					
Stable under normal use conditions					
CONDITIONS TO AVOID:	CONDITIONS TO AVOID:				
Temperatures > 150° C (300°	F), which may soften the copper material.				
REACTIVITY:		INCOMPATIBLE MATERIALS:			
Copper may react with acetylene gas to form copper acetylides, which		Dust is explosively incompatible with			
are sensitive to shock. Copper may react with strong acids to generate		sodium azide.			
explosive gas (e.g. hydrogen)					
HAZARDOUS DECOMPOSITION PRODUCTS:		HAZARDOUS POLYMERIZATION:			
None		The melting of this product may release			
		metal oxides.			
SECTION 11 – TOXICOLOGICAL INFORMATION					
POTENTIAL HEALTH EFFECTS: Symptoms related to the physical, chemical and toxicological characteristics					
Under normal handling and use, exposure to product presents few health hazards. Dusts may cause mechanical					
irritations to eyes and skin. Ingestion may cause transient irritation of throat, stomach and gastrointestinal tract.					
Inhalation may cause coughing, nose and throat irritation, and sneezing. Higher dust exposures may cause difficulty					
breathing, congestion, and chest tightness.					
EYE CONTACT:	If present as dust, copper may cause irritation, discoloration, and damage. As a foreign				
ETE CONTACT.	body in the lens, copper dust may cause a dense cataract and discolor the lens.				

SKIN:	Conner can cause s	ome irritation wi	th nossible c	liscoloration	o of skin
SKIN.	Copper can cause some irritation with possible discoloration of skin.				
	Ingestion of significant amounts of welding electrodes is unlikely. If copper swallowed and person is conscious, give large quantities of water to drink			,	
INGESTION:					arge amounts of dust are
	swallowed.	s possible. Serio	us enects ma	ay occur ir ia	irge amounts of dust are
	Breathing metal dust may worsen symptoms of individuals with pre-existing chr respiratory disease. Follow exposure guidelines for copper dust and fume. Acut				
INHALATION:			• • •	•	irritation, metallic taste in
				-	g copper dust may worsen
	symptoms of indivi		-	-	y disease.
		n Classification o			
Ingredient	t	OSHA	NTP	IARC	Target Organ
None					
TERMS:					
OSHA – Occupational Safety	& Health Administrat	tion			
Y = Listed as a human carc	inogen				
NTP – National Toxicology Pr	-				
K = Known to be a human	-				
R = Reasonably anticipate	•	inogen (RAHC)			
IARC – International Agency		- · ·			
1 = Carcinogenic to humar					
-					
2A = Probably carcinogeni					
2B = Possibly carcinogenic					
3 = Unclassifiable as to car	• ·	ans			
4 = Probably not carcinoge	enic to humans				
Other –					
NL = Not listed					
	SECTION 12	– ECOLOGICAL I			
ECOTOXICITY					D DEGRADABILITY
Not applicable			Not a	pplicable	
BIOACCUMULATION POTENTIAL			MOBI	MOBILITY IN SOIL	
Not applicable			Not a	Not applicable	
OTHER ADVERSE EFFECTS			-		
Copper metal is relatively ins	oluble in water and,	therefore, genera	ally has low I	oioavailabilit	ty. This product is not
expected to present an envir					
	SECTION 13	- DISPOSAL CON	ISIDERATIO	NS	
Recover or Recycle if possible	e. Dispose of according	ng to Federal, Sta	te and Local	Regulations	<ol> <li>Dust collected from</li> </ol>
machining, welding, etc. may be classified as a hazardous waste. Consult Federal, State and Local regulations.					
_ 0. /					-
	SECTION 14	– TRANSPORT II	NFORMATIO	N	
	N			DIAN TRANS	

SECTION 14 – TRANSPORT INFORMATION					
US DEPT OF TRANSPORTATION	CANADIAN TRANSPORTATION OF				
(DOT)-HMR (Hazardous Materials Registration)	DANGEROUS GOODS (TDG)				
Not regulated	Not regulated				
UN SHIPPING NAME	UN NUMBER				
Not regulated	Not regulated				

TRANSPORT HAZARD CLASS	PACKING GROUP				
Not regulated	Not regulated				
ENVIRONMENTAL HAZARDS	LABEL(S) REQUIRED?				
None	No				
TRANSPORT IN BULK	SPECIAL SHIPPING INFORMATION				
Not applicable	Not applicable				
SECTION 15 - REGULATORY INFO	RMATION				
US-OSHA (HAZARD COMMUNICATION STANDARD) References: 29 CFR 1910.1200					
	rd Communication Standard				
A finished casting is an article as defined in the OSHA Haza	ra communication Standard				
29 CFR 1910.1200 (c) 29 CFR 1910.1000 Air Contaminants					
Dust or fumes generated by cleaning, machining, grinding, or welding o	f the casting may produce airborne				
contaminants, such as copper and silica.	The casting may produce and onle				
US-EPA (TOXIC SUBSTANCES CONTROL ACT – TSCA)					
All components of these products are on the TSCA inventory list or are of	excluded from listing				
US-EPA (SARA TITLE III)	excluded normisting.				
Releases to the environment of <b>Copper</b> may be subject to reporting und	der Section 313 of Title III of the Superfund				
Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.	der Seetion 515 of fille in of the Superfund				
CANADA-WHMIS (WORKPLACE HAZARDOUS MATERIALS INFORMATION	I SYSTEM)				
This SDS has been prepared according to the hazard criteria of the Cont	-				
contains the information required by the CPR.					
CANADA DSL (DOMESTIC SUSTANCES LIST) INVENTORY STATUS					
All components of these products are on the DSL Inventory.					
CEPA (CANDIAN ENVIRONMENTAL PROTECTION ACT)					
No components are on the Toxic Substances List.					
EINECS NO. (EUROPEAN INVENTORY OF EXISTING COMMERCIAL CHEMICAL SUBSTANCES)					
All components of these products are on the EINECS list.					
RoHS (RESTRICTION OF CERTAIN HAZARDOUS SUBSTANCES) COMPLIANCE					
Castings comply with RoHS.					
CALIFORNIA PROPOSITION 65 COMPLIANCE					
Copper is not on California's Proposition 65 list. (California Health & Safety Code 25248.5 et seq.)					
US STATE REGULATORY INFORMATION					
Some of the components listed I Section 3 (e.g., Copper) may be covered under specific state regulations.					
SECTION 16 – OTHER INFORMATION					
SDS PREPARED BY	DATE				
The information herein is given in good faith and based on technical	05/2015				
data The Electric Materials Company believes to be reliable. Since the					
conditions of use are outside our control, we assume no liability in					
connection with any use of this information and no warranty,					
expressed or implied is given. Contact the Electric Materials Company					
or its associates for additional information.					

NOTE:	

This data and label information is offered in good faith as typical values and not as a product specification. No warranty either expressed or implied is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally acceptable. However, each user should review the recommendations in specific context of the intended use and determine if they are appropriate.

LABEL Information: We have no current labels for C308.