

SAFETY	DATA	SHEET	(SDS)
--------	-------------	-------	-------

ID: **C80410**

		A GAILED STARE CO.			
			DATE ISSU	JED: 5/24	/2015
SECTION 1 – PRODUCT IDENTIFICATION & COMPANY INFORMATION					
PRODUCT NAME: C80410 COPPER					
OTHER DESIGI	NATION	S:			
PRODUCT IDENTIF	ICATION	N: N/A			
MANUFACTURER'S INFOR	OITAM		THE ELECTRIC MATERIALS COMPANY 50 SOUTH WASHINGTON STREET NORTH EAST, PA 16428		
EMERGENCY PH	ONE NO	o.: 814-725-9621	WEBSITE:	WWW.EL	ECMAT.COM
RECOMMENDED USE AND R Various Castings and Termin		TIONS ON USE:			
		SECTION 2 – HAZARD IDENTIFICA	ATION		
CLASSIFICATION: Industrial Copper Castings are metallic articles that do not present hazards i their original form.			oresent hazards in		
Grinding castings that have not been cleaned or that contain embedded sand may generate significant amounts of dust containing crystalline silica. OTHER INFORMATION: Fumes from hot processes may contain other compounds with different exposure limits. Dust or fumes generated by machining, grinding, welding or thermal cutting of the casting may produce airborne contaminants. Consult Sections 3 & 8 for further information.			lline silica. vith different inding, welding or		
SECTION 3 – COMPOSITION/INFORMATION ON INGREDIENTS					
CHEMICAL NAME		COMMON NAME	CAS	5#	PERCENT WEIGHT
Cu Ag		Copper	7440-		99.8% 0.2%
Ag Silver 7440-22-4 0.2% SECTION 4 – FIRST AID MEASURES				0.270	
EYE CONTACT:	Eye injuries from solid particles should receive immediate medical attention. Dust may be flushed from eyes immediately with large amounts of water, lifting the lower and upper lids occasionally; seek medical attention.				
SKIN CONTACT:	Cuts or abrasions should be treated promptly with thorough cleansing of the affected area. Wash the skin using soap or mild detergent and water. Get medical attention if irritation develops and persists.				
INGESTION:	I: If the product or dust is swallowed, seek immediate medical attention or advice. Do not induce vomiting.				

	If breathing has stopped, perform artificial respiration and obtain medical aid				
INHALATION:	immediately. If breathing is difficult, provide fresh air and seek medical attention as				
	soon as possible.				
	CEA	TION	LE FINEFICIATING MEACURES		
FLANANAADIF			I 5 – FIREFIGHTING MEASURES		
FLAMMABLE			applicable applicable; non-combustible		
EXTINGUISE	HING MEDIA:		• •	or approved for toxic dusts	
For a dust fire in a confined area, use a respirator approved for toxic d and fumes. Do not use water to extinguish fires around operations			• •		
PROTECTION OF FI	REFIGHTERS:		lving molten metal due to the potential for steam explosions.		
THE TESTION OF THE			ACCIDENTAL RELEASE MEASURES	Steam expressions:	
-			y be picked up by hand or other means to b	-	
			the dispersion of dust such as a high efficie		
vacuum, wet dust mop, or w	et clean-up. P	ut re	covered material in a suitable, covered, and	l labeled container.	
	SEC	TION	7 – HANDLING AND STORAGE		
			tain good housekeeping to prevent exposu	 ire to materials and	
RECOMMENDE	ED STORAGE:		nicals that may contaminate or impair the c		
			product does not require special safety pre		
			or to installation. Installation and removal of the product may cause		
PROCEDURES FOR	HANDING:	ехро	xposure to dusts and other materials or chemicals associated with the		
PROCEDURES FOR	TANDLING.	insta	llation (work) environment. Operations such	ch as grinding, cutting,	
burning, and welding may generate dusts or fumes which			nes which may require		
special handling procedures.					
SECTION 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION When machining, heating, or melting, use adequate local (preferably) or general					
		•	o	•	
	exhaust ventilation to ensure that concentrations of dusts or fumes exposure limits. Keep workplace clean and dry (unless wet machini				
ENGINEERING CONTROLS: exposure limits. Reep workplace clean and dry (diffess wet machining is being use capture dust and fume). Train personnel to minimize exposure to hazards during					
	installation and replacement of product. On a regular basis, verify condition and prop			_	
function of equipment in which the product will be installed.					
SUBSTANC	E		ACGIH TLV	OSHA PEL	
SUBSTAINC	. C		mg/m³	mg/m³	
Cu		1	1 (dust)		
		0.2	0.2 (fume)		
Ag SUDDI FAMENTAL INFORMATION		0.1	0.1 SUPPLEMENTAL		
SUPPLEMENTAL INFORMATION Individual protection measures: Use		SUPPLEMENTAL INFORMATION Individual protection measures: Use an	INFORMATION		
appropriate gloves to protect against physical		approved respirator, with the proper	Individual protection:		
hazards. Always wear safety glasses with side		assigned protection factor, whenever	Workers should was		
shields and appropriate hear	-		airborne concentrations of hazardous	before meals and leaving	
when grinding or cutting.	3 .		components exceed exposure limits	work.	
			listed above.		

TERMS: ALL EXPOSURE LIMITS REFERENCED HEREIN ARE 8 HOUR TIMEWEIGHTED AVERAGES (TWA) UNLESS OTHERWISE NOTED.

TLV = THRESHOLD LIMIT VALUE/AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS (ACGIH) mg/m³ = MILLIGRAMS PER CUBIC METER

PERSONAL PROTECTION:

Proper hand and foot protection is recommended

SECTION 9 – PHYSICAL & CHEMICAL PROPERTIES		
APPEARANCE/PHYSICAL STATE:		
Metallic solid with a copper color		
ODOR/ODOR THRESHOLD:	VAPOR DENSITY:	
None	Not volatile	
MELTING/FREEZING POINT:	SPECIFIC GRAVITY: (relative density)	
Approximately 1083°C (1980°F) for copper	$8.9 \text{ g/cm}^3 (0.32 \text{ lb./in}^3) \text{ for copper (water = 1)}$	
BOILING POINT:	VAPOR PRESSURE:	
2500°C (4530°F) for copper	~ 0 mm/Hg	
FLASH POINT:	EVAPORATION RATE:	
Not determined	Not volatile	
FLAMMABILITY:	SOLUBILITY IN WATER:	
Not flammable	Insoluble	
UPPER & LOWER FLAMMABILITY LIMITS:	pH:	
Not applicable	Not applicable	
AUTO IGNITION TEMPERATURE:	VISCOSITY:	
Not applicable	Not applicable	
DECOMPOSITION TEMPERATURE:	PARTITION COEFFICIENT:	
Not applicable	Not applicable	

SECTION 10 – STABILITY & REACTIVITY		
CHEMICAL STABILITY:		
Stable under normal use conditions		
CONDITIONS TO AVOID:		
Temperatures > 150° C (300° F), which may soften the copper material.		
REACTIVITY:	INCOMPATIBLE MATERIALS:	
Copper may react with acetylene gas to form copper acetylides, which	Dust is explosively incompatible with	
are sensitive to shock. Copper may react with strong acids to generate sodium azide.		
explosive gas (e.g. hydrogen).		
HAZARDOUS DECOMPOSITION PRODUCTS:	HAZARDOUS POLYMERIZATION:	
None	The melting of this product may release	
	metal oxides.	
SECTION 11 – TOXICOLOGICAL INFORMATION		

SECTION 11 – TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS: Symptoms related to the physical, chemical and toxicological characteristics Under normal handling and use, exposure to product presents few health hazards. Dusts may cause mechanical irritations to eyes and skin. Ingestion may cause transient irritation of throat, stomach and gastrointestinal tract. Inhalation may cause coughing, nose and throat irritation, and sneezing. Higher dust exposures may cause difficulty breathing, congestion, and chest tightness.

EYE CONTACT:

If present as dust, copper may cause irritation, discoloration, and damage. As a foreign body in the lens, copper dust may cause a dense cataract and discolor the lens.

SKIN:	Copper can cause some irritation with possible discoloration of skin.				
	Ingestion of significant amounts of welding electrodes is unlikely. If copper is swallowed and person is conscious, give large quantities of water to drink. Get medical				
INGESTION:	attention as soon as possible. Serious effects may occur if large amounts of dust are swallowed.				
INHALATION:	Breathing metal dust may worsen symptoms of individuals with pre-existing chronic respiratory disease. Follow exposure guidelines for copper dust and fume. Acute exposure to dust or fume may cause upper respiratory tract irritation, metallic taste in mouth, nausea, fatigue, and/or metal fume fever. Breathing copper dust may worsen symptoms of individuals with pre-existing chronic respiratory disease.				
Carcinogen Classification of Ingredients					
Ingredien	Ingredient OSHA NTP IARC Target Organ				Target Organ
None	one				

TERMS:

OSHA – Occupational Safety & Health Administration

Y = Listed as a human carcinogen

NTP – National Toxicology Program

K = Known to be a human carcinogen

R = Reasonably anticipated to be a human carcinogen (RAHC)

IARC - International Agency for Research on Cancer

1 = Carcinogenic to humans

2A = Probably carcinogenic to humans

2B = Possibly carcinogenic to humans

3 = Unclassifiable as to carcinogenicity to humans

4 = Probably not carcinogenic to humans

Other -

NL = Not listed

SECTION 12 – ECOLOGICAL INFORMATION			
ECOTOXICITY	PERSISTENCE AND DEGRADABILITY		
Not applicable	Not applicable		
BIOACCUMULATION POTENTIAL	MOBILITY IN SOIL		
Not applicable	Not applicable		

OTHER ADVERSE EFFECTS

Copper metal is relatively insoluble in water and, therefore, generally has low bioavailability. This product is not expected to present an environmental hazard. Avoid releasing dusts and fumes into the environment.

SECTION 13 – DISPOSAL CONSIDERATIONS

Recover or Recycle if possible. Dispose of according to Federal, State and Local Regulations. Dust collected from machining, welding, etc. may be classified as a hazardous waste. Consult Federal, State and Local regulations.

SECTION 14 – TRANSPORT INFORMATION			
US DEPT OF TRANSPORTATION	CANADIAN TRANSPORTATION OF		
(DOT)-HMR (Hazardous Materials Registration)	DANGEROUS GOODS (TDG)		
Not regulated	Not regulated		
UN SHIPPING NAME	UN NUMBER		
Not regulated	Not regulated		

TRANSPORT HAZARD CLASS	PACKING GROUP
Not regulated	Not regulated
ENVIRONMENTAL HAZARDS	LABEL(S) REQUIRED?
None	No
TRANSPORT IN BULK	SPECIAL SHIPPING INFORMATION
Not applicable	Not applicable

SECTION 15 - REGULATORY INFORMATION

US-OSHA (HAZARD COMMUNICATION STANDARD)

References: 29 CFR 1910.1200

A finished casting is an article as defined in the OSHA Hazard Communication Standard

29 CFR 1910.1200 (c)

29 CFR 1910.1000 Air Contaminants

Dust or fumes generated by cleaning, machining, grinding, or welding of the casting may produce airborne contaminants, such as copper and silica.

US-EPA (TOXIC SUBSTANCES CONTROL ACT – TSCA)

All components of these products are on the TSCA inventory list or are excluded from listing.

US-EPA (SARA TITLE III)

Releases to the environment of **Copper** may be subject to reporting under Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

CANADA-WHMIS (WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM)

This SDS has been prepared according to the hazard criteria of the Controlled Product Regulations (CPR) and the SDS contains the information required by the CPR.

CANADA DSL (DOMESTIC SUSTANCES LIST) INVENTORY STATUS

All components of these products are on the DSL Inventory.

CEPA (CANDIAN ENVIRONMENTAL PROTECTION ACT)

No components are on the Toxic Substances List.

EINECS NO. (EUROPEAN INVENTORY OF EXISTING COMMERCIAL CHEMICAL SUBSTANCES)

All components of these products are on the EINECS list.

Rohs (RESTRICTION OF CERTAIN HAZARDOUS SUBSTANCES) COMPLIANCE

Castings comply with RoHS.

CALIFORNIA PROPOSITION 65 COMPLIANCE

Copper is not on California's Proposition 65 list. (California Health & Safety Code 25248.5 et seq.)

US STATE REGULATORY INFORMATION

Some of the components listed I Section 3 (e.g., Copper) may be covered under specific state regulations.

SECTION 16 – OTHER INFORMATION			
SDS PREPARED BY	DATE		
The information herein is given in good faith and based on technical	05/2015		
data The Electric Materials Company believes to be reliable. Since the			
conditions of use are outside our control, we assume no liability in			
connection with any use of this information and no warranty,			
expressed or implied is given. Contact the Electric Materials Company			
or its associates for additional information.			

NOTE:

This data and label information is offered in good faith as typical values and not as a product specification. No warranty either expressed or implied is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally acceptable. However, each user should review the recommendations in specific context of the intended use and determine if they are appropriate.

LABEL Information: We have no current labels for C80410.